

SECTION 10

RESIDENTIAL R6 ZONE

10.1 GENERAL PURPOSE OF THE R6 ZONE

These Zone variations provide for and regulate medium density development in various forms of cluster housing from single detached dwellings to townhouses and apartments.

10.2 PERMITTED USES (Section 10.2 added by Z.-1-101921)

"No person shall erect or use any building or structure, or use any land or cause or permit any building or structure to be erected or used, or cause or permit any land to be used, in any Residential R6 Zone variation for any use other than the following uses:

1) R6-1

The following are permitted uses in the R6-1 Zone variation:

- a) Single detached dwelling

2) R6-2

The following are permitted uses in the R6-2 Zone variation:

- a) Single detached dwelling

3) R6-3

The following are permitted uses in the R6-3 Zone variation:

- a) Single detached dwelling;
- b) Semi-detached dwelling;
- c) Duplex dwelling

4) R6-4

The following are permitted uses in the R6-4 Zone variation:

- a) Single detached dwelling;
- b) Semi-detached dwelling;
- c) Duplex dwelling

5) R6-5

The following are permitted uses in the R6-5 Zone variation:

- a) Single detached dwelling;
- b) Semi-detached dwelling;
- c) Duplex dwelling;
- d) Triplex dwelling;
- e) Townhouse dwelling;
- f) Stacked Townhouse dwelling;
- g) Apartment buildings
- h) Fourplex dwelling;

10.3 REGULATIONS

No person shall erect or use any building or structure, or use any land or cause or permit any building or structure to be erected or used, or cause or permit any land to be used, in any Residential R6 Zone variation except in conformity with the regulations as set out below and in Table 10.3 or as set out on the Zoning Maps.

- 1) INTERIOR SIDE YARD AND REAR YARD DEPTH (MINIMUM)
(applies only to the R6-5 Zone Variation (Z.-1-97503)(Z.-1-101921))

0.4 metres (1.3 feet) per 1 metre (3.28 feet) of main building height or fraction thereof, but in no case less than 3 metres (9.8 feet) when the end wall of a unit contains no windows to habitable rooms, or 6.0 metres (19.7 ft.) when the wall of a unit contains windows to habitable rooms.

- 2) Only one dwelling is permitted to be constructed on a unit in a Vacant Land Condominium.

No dwellings are permitted to be constructed within a proposed Vacant Land Condominium until after registration of the plan of condominium has occurred, except for a single detached dwelling.

No attached dwellings are permitted to be constructed within a proposed Vacant Land Condominium until after registration of the plan of condominium has occurred (Z.-1-142295)

10.4 SPECIAL PROVISIONS

The following zones apply to unique or existing situations and are not the standard R6 Zones. If a regulation or use is not specified, the list of permitted uses and/or the regulations of Section 10.2 and/or Section 10.3 shall apply.

a) R6-1 Zone Variation

R6-1(1)

a) Regulations:

- i) Lot Area 4 000 square metres
(Minimum): (43,057 square feet.
(O.M.B. File #R910387 - Appeal #7027 June 4, 1993)

R6-1(2) 505 Jarvis Street

a) Regulations:

- i) Number of cluster single detached units 10
(Maximum):
(Z.-1-93153)(O.M.B. File # R 930207, March 8, 1994)

R6-1(3) (Z.-1-96456 deleted at Council on November 4, 1996)

R6-1(4)

a) Regulations

- i) Rear Yard Depth 25.0 metres (82.02 ft)
(Minimum):
(Z.-1-97536)

R6-1(5)

a) Regulations:

- i) Number of cluster single Detached Dwellings (Maximum): 29 units
(Z.-1-99676 - O.M.B. Order No. 2207 - O.M.B. File # R 990140 (Order date: December 3,1999)

R6-1(6)

a) Regulations

- i) Number of Cluster Single Detached Dwellings (Maximum): 3 units
- ii) Setback from North Property Line 21 metres (68.9 feet)
(Minimum):
(Z.-1-00842 - Decision No. 1578 - October 27, 2000)

R6-1(7)

a) Regulations:

- i) Notwithstanding the provisions of Table 10.3 of this By-law to the contrary, the maximum density calculation for lands zoned R6-1(7) shall be based on a developable lot area of 3 hectares (7.4 acres), and shall be calculated at maximum density of 5 units per hectare.
- ii) Notwithstanding the provisions of Table 10.3 of this By-law to the contrary, the minimum interior side yard and/or rear yard for any structure shall be 1.8 metres (6 feet) from any property or zone boundary. The rear lot line is deemed to be the lot line that abuts the OS5(4) Zone variation.
- iii) Notwithstanding the provisions of Table 10.3 of this By-law to the contrary, the maximum lot coverage shall include lands within the abutting Open Space OS5 (4) Zone.
(Z.-1-021010)

R6-1(8)

a) Regulations:

- i) Rear Yard Depth for Structures or Accessory Buildings (Minimum): 15.0 metres (49.2 ft) for Structures or to e the property line.
(Z.-1-021039)

R6-1(9)

a) Regulations:

- i) The maximum density of 10 units per hectare for the lands zoned R6-1(9) shall be based on the total lot area of 1.6 hectares (4 acres).
- ii) Lot Frontage (Minimum): 11 metres (36 feet)
(Z.-1-051375)

R6-1(10)

a) Regulations:

- i) Rear Yard Depth for Structures or Accessory Buildings adjacent to the OS5 Zone along the north and east boundary (Minimum): 10 metres (32.8 feet)
- ii) Density (Maximum): 11 units per hectare based on a lot area of 0.76 hectares (1.9 acres) to a total of 8 dwelling units.
(Z.-1-051438)

- R6-1(11)
- a) Regulations:
- i) Front and Exterior Side Yard Depth (Minimum) (Z.-1-061496) 2.0 metres (6.56 ft.)
- R6-1(13)
- a) Regulations:
- i) Density (Maximum) Three (3) units
- ii) Lot Frontage (Minimum): 19 metres
- iii) Setback to an Open Space Zone (Minimum): (Z.-1-091855) 22 metres
- R6-1(14)
- a) Regulations
- i) Lot Frontage 20 m
- ii) Number of Cluster Single Detached Dwelling Units (Maximum): (Z.-1-122111 –OMB Order PL100093 May 25, 2012) 21
- R6-1(15)
- a) Regulations
- i) Number of Cluster Single Detached Dwellings (Maximum): (Z.-1-162641 – OMB Order PL 141425) 5 units
- R6-1(16) 2054 Adelaide Street North
- a) Regulations:
- i) Front Yard Setback, Main Dwellings (Minimum): 3 metres (9.8 feet)
- ii) Front Yard Depth for Garages (Minimum): (Z.-1-192775 - LPAT Issued - 2018-11-05) 5.5 metres (18.0 feet)
- R6-1(17) Number not used
- R6-1(18) 704 and 706 Boler Road
- (a) Regulations
- i) Minimum Block Frontage 12 m (39.37 ft.)
- ii) Minimum Landscaped Open Space for Block 35%
- iii) Maximum Block Coverage 40%
- iv) Maximum Building Height 10.5 m (34.45 ft.)
- v) Maximum Density for Block (units per hectare) 9.75 UPH
- vi) Maximum Number of Cluster Single-Detached

- | | | |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| | Units within Block | 13 units |
| vii) | Minimum Lot Area for any Cluster Single Detached Unit | 500 m ² |
| viii) | Maximum of two Cluster Single Detached units shall abut 1105 Cherrygrove Drive | |
| ix) | Minimum Rear Yard setback of Cluster Single Detached Unit abutting 1105 Cherrygrove Drive shall be 10 m (32.81 ft.), save and except from the mutual property line located at the northwest corner of 1105 Cherrygrove Drive southerly for a distance of 20 m (65.62 ft.) wherein the rear yard setback shall be 7.5 m (24.61 ft.). (Z.-1-202860 – LPAT Order PL160298 – January 24, 2020) | |

b) R6-2 Zone Variation

R6-2(1)

- a) Regulations
- i) The regulation for minimum separation distance between dwellings is 2.3 metres in the case of dwelling units containing attached garages, in all other cases the minimum separation distance shall be 3.0 metres.
 - ii) Height (Maximum): 6.0 metres (19.7 feet)
(Z.-1-97494 - O.M.B. File No. Z 950127 (Order Issue Date July 26, 1996))

R6-2(2)

- a) Regulations:
- i) The minimum lot frontage, which shall be at the north end of the development block adjacent to the future extension of Shore Road or other road network, shall be 16 metres (52.5 feet). Should no open road exist at this location at the time of development, the block shall be deemed to comply with the frontage requirement provided there is a temporary easement to the benefit of the developer across a 0.3 metre (1 foot) reserve to Oxford Street West, constructed and dedicated as a public highway. (Z.-1-021045)

R6-2(3)

- a) Regulations:
- i) Lot Frontage (Minimum): 18 metres (59 feet)
(Z.-1-031071)

R6-2(4)

- a) Regulations:
- i) Lot Frontage (Minimum): 18 metres (59 feet)
(Z.-1-031072)

R6-2(5)

- a) Regulations:
- i) Interior Side Yard from west limit of property line (Minimum): 10 metres (32.8 feet)

- ii) Lot Coverage (Z.-1-041210) 35%

6)

R6-2(7)

a) Regulations:

- i) Number of Cluster Single Detached Dwellings (Maximum): 11 units

R6-2(8)

a) Regulations:

- i) Total number of units: 58
(Z.-1-081723 – O.M.B. Issue Date September 11, 2008 – PL 080569)

R6-2(9)

a) Additional Regulations:

- i) Lot Frontage (Minimum): 16.0 metres
- ii) Maximum Number of Dwelling Units: Seven (7)
(Z.-1-081803)

R6-2(10)

a) Regulations:

- i) West Interior Side Yard: 6.0 metres (19.7 feet), except the northerly 43.0 metres of the west property line being measured from the north property line, which shall be 10.0 metres (32.8 feet)
- ii) Rear Yard: 6.0 metres (19.7 feet), except the most easterly 18.0 metres of the north property line being measured from the east property line, which shall be 9.0 metres (29.5 feet)
- iii) East Interior Side Yard: 3.0 metre (9.8 feet), except the most northerly 13.0 metres of the east property line being measured from the north property line, which shall be 6.0 metres (19.7 feet)
- iv) No accessory building or structure, other than an accessory building or structure which is less than 10 square metres (108 square feet), shall be located within the required west and east interior side yard and the required rear yard as detailed in parts i), ii), and iii).
(Z.-1-111984 – OMB Case # PL 110249)

- R6-2(11) 2835 Sheffield Place
- a) Regulations:
- i) Lot Frontage (Minimum): 12.0 metres
 - ii) Rear Yard Depth (Minimum): 4.5 metres
 - iii) Interior Side Yard Depth (Minimum): 3.0 metres
 - iv) Lot Coverage (Maximum): 35%
(Z.-1-192726)
- R6-2(12)
- a) Regulations:
- i) Front and Exterior Side Yard Depth (Minimum): 4.5 metres (14.76 ft)
(Z.-1-112020)
- R6-2(13)
- a) Regulations:
- i) Lot Frontage (Minimum): 10.0 metres
 - ii) East Interior Side Yard (Minimum): 1.2 metres
(Z.-1-122117)
- R6-2(14)
- a) Regulations:
- i) Sideyard Setback (Minimum): 1.2 Metres
(applies to units 8 and 16 Only in plan 39CD-12512)
 - ii) Coverage: 40% (max)
 - iii) Rear Yard (Z-1-132158): 8 metres (min)
- R6-2(15)
- a) Regulations
- i) Lot Frontage (Minimum): 8.0 metres
 - ii) Density (Maximum): 22 units per hectare
(Z.-1-182691)
- c) R6-3 Zone Variation**
- R6-3(1)
- a) Regulations:
- i) Main Building Setback from Existing Imperial Oil Pipeline (Minimum): 20 metres (65 feet)
(Z.-1-00836 - O.M.B. Decision # 2184 - December 1, 1999))

R6-3(2)

R6-3(3)

- a) Regulations:
- i) Lot Area (Minimum): 8 000 square metres (2 acres)
 - ii) Lot Frontage (Minimum): 75 metres (246 feet)
 - iii) Landscaped Open Space (Minimum): 45%
 - iv) Lot Coverage (Maximum): 30%
 - v) Height (Maximum): 7 metres (23 feet)
 - vi) Front Yard Setback (Minimum): 3 metres (9.8 feet)
 - vii) Rear Yard Setback (Minimum): 7 metres (23 feet) (Z.-1-041301)

R6-3(4)

- a) Regulations:
- i) No. of units (Maximum): 5 units
 - ii) Lot Frontage (Minimum): 20 metres
 - iii) Minimum sideyard: 3.0 metres (for an exterior sideyard with windows to habitable rooms) (Z.-1-061446)

R6-3(5)

- a) Regulations:
- i) A maximum of five (5) residential units served by individual, on-site waste water treatment systems may be permitted until such time as municipal sanitary sewer services are available.
 - ii) Density (Maximum): 16 units per hectare based on a total lot area of 0.34 hectares (0.84 acres) to a total of 5 dwelling units.
 - iii) Lot Frontage (Minimum): 20 metres (65.6 feet)
 - iv) Lot Area (Minimum): 3,400 square metres (36,597 square feet) (Z.-1-061573)

R6-3(6)

- a) Regulation:
- i) Lot Frontage (Minimum): 18 metres (59 feet) (Z.-1-091867)

R6-3(7)

- a) Regulations:
- i) Front Yard Depth (m) (Minimum): 3.0 metres (9.8 ft.)
 - ii) Rear Yard Depth (m) (Minimum): 4.5 metres (14.7 ft.) for one storey building.
 - iii) Interior Side Yard Depth (Minimum): 1.2 metres (3.9 ft.) plus, for any portion of the side yard adjacent to a part of the building exceeding one storey in height, 0.6 metres (2.0 ft.) for each storey or part thereof above one storey.
 - iv) Lot Coverage (%) (Maximum): (Z.-1-111979) 40

R6-3(8) 7 Annadale Drive

- a) Permitted Uses:
- i) cluster single detached dwellings
 - ii) cluster townhouse dwellings
- b) Regulations:
- i) Lot Area (Minimum): 1 ha. (2.47 ac)
 - ii) Lot Frontage (Minimum): 14 metres (45.9 feet)
 - iv) Interior side and rear yard depth (abutting a Residential R1-8 Zone) Variation (Minimum): 10 metres (32.8 feet)
 - v) Interior side and rear yard depth (abutting a Residential R1-5 Zone Variation (Minimum): 4.5 metres (14.8 feet)
 - vi) Interior side and rear yard depth (abutting a Open Space (OS1) Zone Variation (Maximum): 2.0 metres (6.6 feet)
 - vii) Landscaped Open Space (Minimum) 50%
 - viii) Lot Coverage (%) (Maximum): 25%
 - ix) Height (m) (Maximum) half 2 storeys, or 9 metres whichever is less with no storeys being permitted for basements
 - x) Density (Maximum) 25 units per hectare
 - xi) The front face and primary entrance of dwellings abutting an Open Space (OS1) zone shall be oriented towards the Open Space (OS1) Zone. (Z.-1-142357)

- xii) No part of any required interior side yard or rear yard shall be used for any purpose other than landscaped open space

d) R6-4 Zone Variation

R6-4 (1)

a) Regulations:

- i) The property at 195-197 Barker Street may have a frontage requirement of 10.0 metres (32.8 feet), the separation between dwellings requirement is deleted, and the maximum landscaped open space at 30%.
(Z.-1-91032)

R6-4(2)

a) Regulations

- i) Lot Frontage 20 metres (66 feet)
(Minimum):
(Z.-1-95391 - O.M.B. Order Z 950026 (Order Issue Date: October 25, 1995)

R6-4(3) (Added by By-law Z.-1-96404 and deleted by Z.-1-97503)

R6-4(4)

a) Regulations

- i) Setback from a Railway Right-of-Way 15 metres (49.2 feet)
(Minimum)
- ii) Setback from a Railway Right-of-Way means the shortest horizontal distance between the nearest boundary of a railway right-of-way and the nearest part of any residential building.
(Z.-1-96408)

R6-4(5)

a) Regulations:

- i) Dwelling Setback From Railway Right-of-Way 120 metres (394 feet) in the absence of a safety berm, combination safety berm and acoustic fence, adjoining and parallel to railway right-of-way, or 30 metres (98 feet) in conjunction with the safety/acoustic berm noted above. (Z.-1-99702)

R6-4(6)

a) Regulations:

- i) Lot Frontage 18.0 metres (59 feet)
(Minimum):
(Z.-1-99697)

R6-4(7)

a) Regulations

- i) There shall be no minimum lot frontage requirement.
- ii) The maximum density calculation shall be based on a total lot area of 5.65 hectares (14 acres), which includes lands in the abutting OS5(4) and OS1 Zone variations.

- iii) The minimum interior side yard and/or rear yard for any structure with a basement shall be 20 metres (65.6 feet) from the northwest property boundary or 20 metres (65.6 feet) from any Open Space OS5 Zone variation, whichever is greater. The rear lot line is deemed to be the lot line that abuts any OS5 or UR Zone variation.
- iv) Access may be permitted via a private right-of-way to the improved street of North Centre Road.
(Z.-1-00815)

R6-4(8)

- a) Regulations:
 - i) Main building setback of 20 metres (65 feet) minimum from the centre of the existing Imperial Oil pipeline.
(Z.-1-00836 - O.M.B. Decision # 2184 - December 1, 1999)

R6-4(9)

- a) Regulations:
 - i) The maximum lot coverage calculation shall be based on the total block area which includes lands within the block which are zoned OS5(4) at a width of 3.0 metre (9.8 feet).
(Z.-1-01869)

R6-4(10)

- a) Regulations:
 - i) Setback from Industrial Zoned Lands (Minimum): 15 metres (49.2 feet)
(Z.-1-01896)

R6-4(11)

- a) Additional Permitted Use:
 - i) Converted dwellings.
- b) Regulations:
 - i) Density (Maximum): 39 units per hectare
 - ii) Height (Maximum) : 1 storey
(Z.-1-021066)

R6-4(12)

- a) Regulations
 - i) Number of units (Maximum): 24 units
 - ii) Lot Frontage (Minimum): 0 metres
 - iii) Access to site: To be provided via Beaufort Street (not assumed road)
 - iv) Interior side yard Depth (Minimum): 3 metres (9.8 feet)
 - v) Rear Yard Depth (Minimum): 3 metres (9.8 feet)
(Z.-1-031099 - O.M.B. File No. Z 020010 - Order Issue Date: March 14th,2003)

R6-4(13)

- a) Regulations:
- i) Dwelling Setback From High Pressure Pipeline (Z.-1-041233) 20 metres (66 feet)

R6-4(14)

- a) Permitted Uses:
- i) Cluster single detached dwellings;
 - ii) Cluster semi-detached dwellings; and
 - iii) Cluster duplex dwellings.
- b) Regulations:
- i) Lot Area (Minimum) 0.60 hectares (1.4 acres)
 - ii) Lot Frontage (Minimum) 70.0 metres (229.6 feet)
 - iii) Lot Coverage (Maximum) 35%
 - iv) Density (Maximum) 30 units per hectare
 - v) Height (Maximum): 10.5 metres (34.4 feet)
 - vi) Front Yard Setback (Minimum) : 3.0 metres (9.8 feet)
 - vii) Rear and Interior Yard Setbacks Abutting Residential Zones (Minimum): 7.5 metres (24.6 feet)
 - viii) Yards Where Parking Area Prohibited (Z.-1-041291) Parking is prohibited in the side and rear yard butting existing residential development

R6-4(15)

- a) Regulations:
- i) Lot frontage: (Minimum) 10 metres
 - ii) Coverage (Maximum) 45%
 - iii) Interior sideyard (Minimum) 1.2 metres
 - iv) Height (Maximum) (Z.-1-091880) 12 metres

R6-4(16)

- a) Regulations
- i) Front Yard Setback, Main Dwellings (Minimum): 3 metres (9.8 feet)
 - ii) Front Yard Depth for Garages(Minimum.): (Z.-1-142328) 5.5 metres (18.0 feet)

R6-4(17)

- a) Regulations
 - i) Front Yard Setback, Main Dwellings (Minimum): 3 metres (9.8 feet)
 - ii) Front Yard Depth for Garages (Minimum): 5.5 metres (18.0 feet)
 - iii) Notwithstanding the provisions of Section 2 "LOT LINE, FRONT", the frontage for this lot will be deemed to be along the secondary collector. (Z.-1-142328)

R6-4 (18)

- a) Additional Regulations:
 - i) Frontage (Minimum) 20 metres (65.6 feet)
 - ii) Setback to Wonderland Rd 3 metres (9.8 feet) (Minimum) (Z.-1-152415)

e) R6-5 Zone Variation

R6-5(1)

- a) Regulations
 - i) Setback from railway right-of-way with safety and noise berm (Minimum) 15 metres (49.2 feet) (Z.-1-94266)

R6-5(2) (Deleted by Z.-1-97503)
(Z.-1-94276 - O.M.B. File # O 940190 and R 940364 (February 20, 1995))

R6-5(3)

- a) Additional Permitted Uses
 - i) Converted Dwellings
- b) Regulations for Existing Buildings
 - i) Front Yard (Minimum) Existing
 - ii) Separation Between Buildings on a Lot (Minimum) Existing
- c) Regulation for Single, Semi-detached, Duplex, Triplex, Townhouse, Stacked Townhouse and Apartment Buildings
 - i) Rear Yard Depth Abutting an Open Space Zone (Minimum) 2.0 metres (6.6. feet) (Z.-1-95303)

R6-5(4)

- a) Regulation
 - i) The regulation for a minimum separation distance between dwellings is not applicable. (Z.-1-97469)

R6-5(5)

- a) Regulations:
 - i) Lot Frontage (Minimum) (Z.-1-00812 and Z.-1-00814) 22 metres (72 feet)

R6-5(6)

- a) Regulations:
 - i) The maximum density calculation shall be based on a total lot area of 2.44 hectares (6 acres), which includes lands in the abutting OS1 Zone variation. (Z.-1-00815)

R6-5(7)

- a) Additional Permitted Use:

Permitted uses may be developed in the form of land lease community homes. (Z.-1-01891)
- b) Regulations:
 - i) Density (Maximum) 30 units per hectare (12 units per acre)
 - ii) Setbacks from any OS2 Zone Variation (Minimum) 1 metre (3.2 feet)
 - iii) Setbacks from any OS5 Zone Variation (Minimum) 10 metres (32.8 feet)
 - iv) Height for apartment buildings (Maximum) 27 metres (88.5 feet)
 - v) Setbacks for apartment buildings from Kains Road (Minimum) 200 metres (656 feet)
 - vi) Setbacks for apartment buildings from any OS5 Zone Variation (Minimum) (Z.-1-00834) 75 metres (246 feet)
 - vii) Lot Area (Minimum) (Z.-1-01891) 42.5 hectares

R6-5(8)

- a) Regulations:

Notwithstanding the provisions of Section 3.9 2) a) of this By-law to the contrary, the maximum density calculation for the lands zoned R6-5(8) shall be based on a lot area of 1.33 hectares (3.29 acres) which includes the lands in the abutting Open Space Special Provision (OS5(5)) Zone. (Z.-1-01876)

- R6-5(9)
- a) Regulations:
- i) Front and Exterior Yard Depth for Main Dwelling To Local and Secondary Collector Roads (Minimum): 4.5 metres (14.8 feet)
 - ii) Front and Exterior Yard Depth for Garages (Minimum): (Z.-1-01911) 6 metres (19.7 feet)
- R6-5(10)
- a) Regulations:
- i) Lot Frontage (Minimum) (Z.-1-031130) 22 metres (72 feet)
- R6-5(11)
- a) Regulations:
- i) Lot Frontage (Minimum) (Z.-1-031131) 22 metres (72 feet)
- R6-5(12) (Z.-1-031134 was repealed by Z.-1-031136)
- R6-5(13)
- a) Regulations:
- i) Lot Frontage: (Minimum) (Z.-1-031145) 22 metres (72 feet)
- R6-5(14)
- a) Regulations:
- i) Setback from a Railway right-of-way 120 metres (394 feet) in the absence of a safety berm, 30 metres (98.4 feet) in conjunction with a safety berm. (Z.-1-041202)
- R6-5(15)
- a) Regulations:
- i) Lot Frontage (Minimum) 22 metres (72.1 feet)
 - ii) Setback from OS5 Zone (Minimum) (Z.-1-041232) 10 metres (32.8 feet)
- R6-5(16)
- a) Regulations:
- i) Dwelling Setback From High Pressure Pipeline (Minimum) 10 metres (66 feet)

- ii) Lot Area (Minimum) 2,000 square metres (21,528 square feet)
 - iii) Lot Frontage (Minimum) (Z.-1-041233) 22 metres (72 feet)

- R6-5(17)
 - a) Permitted Uses:
 - i) Single detached dwellings;
 - ii) Semi-detached dwellings;
 - iii) Duplex dwellings;
 - iv) Triplex dwellings;
 - v) Stacked townhouses;
 - vi) Townhouses. (Z.-1-041257)

- R6-5(18)
 - a) Regulations:
 - i) Lot Frontage (Minimum): (Z.-1-041270) 20 metres (65.6 feet)

- R6-5(19)
 - a) Regulations:
 - i) Density for Cluster Stacked Townhouse Dwellings (Maximum): 65 units per hectare
 - ii) Where the lands to which this special provision zone applies are used for a combination of cluster stacked townhouses and any other type of cluster housing permitted by this zone, the maximum number of stacked dwelling units permitted by the density regulation in part (i) above shall be reduced at the rate of one dwelling unit for each of the other type(s) of cluster housing units proposed for development. (Z.-1-041307)

- R6-5(20)
 - a) Regulations:
 - i) Dwelling Setback Right of Way combination (Minimum): 120 metres (394 feet) in the absence of a safety berm and acoustic fence adjoining and parallel to the rail right of way, or 30 metres (98 feet) in conjunction with the safety/acoustic berm noted above. (Z.-1-061478)

- R6-5(21)
 - a) Regulations:
 - i) Habitable Building Setback from the centreline of the petroleum products pipeline (Minimum) (Z.-1-061523) 20 metres (66 feet)

R6-5(22)

- a) Permitted Uses:
- i) Cluster housing, in the form of single detached dwellings, semi-detached dwellings, duplex dwellings, triplex dwellings, townhouse dwellings and stacked townhouse dwellings.
 - ii) Permitted uses may be developed in the form of land lease community homes.
- b) Regulations:
- i) Density (Maximum) 30 units per hectare (12 units per acre)
 - ii) Setback from any OS2 Zone Variation (Minimum) 1 metre (3.2 feet)
 - iii) Setbacks from any OS5 Zone Variation (Minimum) (Z.-1-061567) 10 metres (32.8 feet)

R6-5(23)

- a) Permitted Uses:
- i) Triplex
 - ii) Fourplex
 - iii) Townhouse
 - iv) Stacked Townhouse: and
 - v) Apartment Buildings
- b) Regulations
- i) Lot Area Minimum 850 m²
 - ii) Lot Frontage (m) Minimum 10 metres
 - iii) Front and Exterior (minimum): 0.0 m
 - iv) Side Yard Depth (m) (maximum): 3.0 m
For 1st and 2nd Storey
 - v) Front and Exterior the Sideyard Setback for 3rd Storey and above 1.0 metre (max/min) plus setback established for the 1st and 2nd storey's
 - vi) Rear Yard Depth (m) Minimum 0.5 metre (1.6 feet) per 1.0 metre (3.3 feet) of main building height or fraction thereof, but in no case less than 3.0 metres (9.8 feet) when the wall of a unit contains no windows to habitable rooms or 6 m (19.7 feet) when the wall of a unit contains windows to habitable rooms.
3.0 metres (9.8 feet) where the wall of an end unit facing the rear yard and/or interior side yard

contains windows to habitable rooms on the ground floor only and no access points to the dwelling unit along the wall facing rear yard or interior side yard.

- vii) Setback from Open Space Zone Minimum 1.0 metre
- viii) Landscaped open space (%) minimum 30%
- ix) Lot coverage (%) maximum 45%
- x) Height (m) Maximum 15.0 metres
- xi) Density-units (minimum): 30 units per hectare
(maximum): 75 units per hectare
Z.-1-132169

R6-5(24)

a) Permitted Uses:

- i) Triplex
- ii) Fourplex
- iii) Townhouse
- iv) Stacked Townhouse; and
- v) Apartment buildings

b) Regulations:

- i) Lot Area (Minimum) 850 m²
- ii) Lot Frontage (m) (Minimum) 10 metres
- iii) Setback for 1st and 2nd Store front any street and from An open space zone depth (m) 0.0 m minimum
3.0m maximum
- iv) Setback for 3rd storey and above 1.0 metre (max/min) plus the Setback established for the 1st and 2nd storey's
- v) Interior yard depth (m) Minimum 0.5 metre (1.6 feet) per 1.0metre (3.3 feet) of main building height or fraction thereof, but in no case less than 3.0 metres (9.8 feet) when the wall of a unit contains no windows to habitable rooms or 6.0 metres (19.7 feet) when the wall of a unit contains windows to habitable rooms.

3.0 metres (9.8 feet) where the wall of an end unit facing the rear yard and/or interior side yard contains windows to

habitable rooms on the ground floor only and no access points to the dwelling unit along the wall facing rear yard or interior side yard.

- vi) Landscaped open space (%) minimum: 30%
- vii) Lot coverage (%) maximum 45%
- ix) Height (m) Maximum 15.0 metres
- x) Density-units per (minimum) Hectare 30 units per hectare
- xi) Hectare (maximum) (Z.-1-132169) 75 units per hectare

R6-5(25)

a) Permitted Uses

- i) Single;
- ii) semi-detached;
- iii) duplex
- iv) Triplex;
- v) fourplex;
- vi) townhouse;
- vii) stacked Townhouse;
- viii) and apartment buildings

b) Regulations

- i) Lot Area Minimum 850 m²
- ii) Lot Frontage (m) Minimum 10.0 metres
- iii) Front yard depth (m) 6.0 metres
- iv) Interior and Rear yard Depth (m) minimum 0.5 metre (1.6 feet) per 1.0 metre (3.3 feet) of main Building height or fraction but in no case less than 3.0 metres (9.8 feet) When the wall of a unit Contains no windows to Habitable rooms or 6.0 Metres (19.7 feet) when the Wall of a unit contain Windows to habitable rooms.
3.0 metres (9.8 feet) where the wall of an end unit facing the rear yard and/or interior side yard contains windows to habitable rooms on the ground floor only and no access points to the dwelling unit along the wall facing rear yard or interior side yard.

R6-5(26)

- a) Permitted Uses
 - i) Triplex;
 - ii) fourplex;
 - iii) townhouse
 - iv) Stacked townhouse;
 - v) and Apartment buildings
- b) Regulations
 - i) Lot Area Minimum 850 m²
 - ii) Lot Frontage (m) Minimum 10.0 metres
 - iii) Front Yard Depth (m) For 1st and 2nd storey 0.0 m minimum
3.0 m maximum
 - iv) Front yard setback for 3rd storey and For the 1st and 2nd storey's 1.0 metre (max/mim) plus above the setback established
 - v) Setback to imperial Oil pipeline easement Minimum 20 metres from centreline of pipeline
 - vi) Rear and Interior Yard Depth (m) Minimum 0.5 metre (1.6 feet) per 1.0 metre (3.3 feet) of main building height or fraction thereof, but in no case less than 3.0 metres (9.8 feet) when the wall of a unit contains no windows to habitable rooms or 6.0 Metres (19.7 feet) when the wall of a unit contains windows to habitable rooms 3.0 metres (9.8 feet) where the wall of an end unit facing the rear yard and/or interior Side yard contains windows to habitable rooms on the ground floor only and no access points to the dwelling unit along the wall facing rear yard or interior side yard.
 - vii) Landscaped open space (%) Minimum 30%
 - viii) Lot Coverage (%) maximum 45%
 - ix) Height (m) Maximum 15.0 metres
 - x) Density-units per hectare (minimum) (maximum) 30 units per hectare
75 units per hectare
(Z.-1-081786)/ Z.-1-132169

R6-5(27)

| | | |
|----------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| R6-5(28) | | |
| a) | Additional Regulations: | |
| i) | Density – Units Per Hectare (Minimum) (Z.-1-091882) | 45 units per hectare (14 units per acre) |
| R6-5(29) | | |
| a) | Regualtions: | |
| i) | Denisty – Units Per Hectare (Minimum) | 35 units per hectare |
| ii) | Denisty – Units Per Hectare (Maximum) (Z.-1-091883) | 60 units per hectare |
| R6-5(30) | | |
| a) | Regulations | |
| i) | Setback from Arterial minimum | For all portions of a building road minimum above 9 metres (29.5 ft.) height, the required setback shall be 60 metres. |
| ii) | Dwelling setback from High Pressure Pipeline (Minimum) | 20 metres (66ft.) |
| iii) | Density (Maximum) (Z.-1-122109) | 55 units per hectare |
| R6-5(31) | | |
| a) | Regulations: | |
| i) | Front and Exterior Side Yard Depth (Minimum) (Z.-1-112020) | 4.5 m (14.76) |
| R6-5(32) | | |
| a) | Regulations: | |
| i) | Front and Exterior Side Yard Depth (Minimum) (Z.-1-112020) | 4.5 m (14.76) |
| b) | Regulations: | |
| i) | Lot Frontage (Minimum) | 18 m (59.06) |
| ii) | Lot Area (Minimum) (Z.-1-112060) | 1.7 hectares (4.2 ac) |

- R6-5(34) 2250 Blackwater Road & 660 Garibaldi Avenue
- a) Regulations
- i) Density (Maximum) 63 units per hectare (25 units per acre)
 - ii) Height (Maximum) 12 meters (39.4 feet)
 - iii) The maximum density calculation shall be based on the total block area which existed on the date of the passing of the By-law. (Z.-1-142290)
- R6-5(35) 670 Garibaldi Avenue
- a) Regulations
- i) South Interior Yard (Minimum): 8.3 metres (27.2 feet)
 - ii) Rear Yard from Adelaide Street (Minimum): 10 metres (32.8 feet)
 - iii) The maximum density calculation shall be based on the total block area which existed on the date of the passing of the By-law. (Z.-1-142290)
- R6-5(36)
- a) Regulations
- i) Front Yard Setback, Main Dwellings (Minimum): 3 metres (9.8 feet)
 - ii) Front Yard Depth for Garages (Minimum.): 5.5 metres (18.0 feet)
 - iii) Rear Yard Setback (Minimum): 3 metres (9.8 feet)
 - i) Notwithstanding Section 3.9(2), the maximum density calculation shall be based on a lot area of 2.43 hectares, which includes the lands in the abutting Open Space Special Provision (OS4(10)) Zone. (Z.-1-142328)
- R6-5(37)
- a) Regulations
- i) Front Yard Setback, Main Dwellings (Minimum): 3 metres (9.8 feet)
 - ii) Front Yard Depth for Garages (Minimum): 5.5 metres (18.0 feet)
 - iii) Rear Yard Setback (Minimum): 3 metres (9.8 feet)
 - iv) Notwithstanding Section 3.9(2), the maximum density calculation shall be based on a lot area of 2.46 hectares, which includes the lands in the abutting Open Space Special Provision (OS4(10)) Zone. (Z.-1-142328)

| | | |
|----------|---------------------------------------------------------------------|--------------------------|
| R6-5(38) | | |
| | i) Front Yard Setback, Main Dwellings (Minimum): | 3 metres (9.8 feet) |
| | ii) Front Yard Depth for Garages (Minimum): (Z.-1-142328) | 5.5 metres (18.0 feet) |
| R6-5(39) | 299 Tartan Drive | |
| | a) Regulations: | |
| | i) Front Yard Setback: (Minimum) (Z.-1-142336) | 4.0 m (13.12ft) |
| R6-5(40) | | |
| | a) Regulations: | |
| | i) Front Yard Setback (Minimum): | 4 metres (13.1 feet) |
| | ii) East Interior Side Yard Setback (Minimum): | 4 metres (13.1 feet) |
| | iii) Density (Maximum): (Z.-1-152404) | 40 units per hectare |
| R6-5(41) | 1156 Dundas Street | |
| | a) Additional Permitted Uses: | |
| | i) Continuum-of-Care Facility | |
| | ii) Retirement Homes | |
| | iii) Senior Citizen apartment buildings | |
| | b) Regulations: | |
| | i) Parking Standard for Senior Citizen Apartment Building (Minimum) | 0.25 spaces per unit |
| | ii) Parking Standard for Cluster Townhouses (Minimum) | 1 parking space per unit |
| | iii) Parking Standard for Apartment Buildings (Minimum) | 1 parking space per unit |
| | iv) Density (Maximum) (Z.-1-162440) | 125 units per hectare |
| R6-5(42) | | |
| | a) Regulations: | |
| | i) Front & Exterior Side Yard Depth to Main Building (Minimum): | 3.0 Metres |
| | ii) Lot Coverage (Maximum): (Z.-1-162444) | 50% |

| | | |
|----------|--------------------------------|------------------------|
| R6-5(43) | a) Regulations: | |
| | i) Density | |
| | (Minimum): | 14 units per hectare |
| | (Maximum): | 30 units per hectare |
| R6-5(44) | a) Regulations: | |
| | i) Density | |
| | (Minimum): | 18 units per hectare |
| | (Maximum): | 30 units per hectare |
| | ii) Height | 10.5 metres (34.4 ft) |
| | (Maximum): | |
| R6-5(45) | a) Regulations: | |
| | i) Density | |
| | (Minimum): | 30 units per hectare |
| | (Maximum): | 35 units per hectare |
| | ii) Height | 10.5 metres (34.4 ft) |
| | (Maximum) | |
| R6-5(46) | a) Regulations: | |
| | i) Density | |
| | (Minimum): | 70 units per hectare |
| | (Maximum): | 75 units per hectare |
| | (#’s 43-46 Z.-1-162448) | |
| R6-5(47) | a) Regulations: | |
| | i) Front Yard Setback | 1.5 metres (min) |
| | (applies to unit 14) | |
| | only in plan 39CD-16503) | |
| | ii) Front Yard Setback | 2.5 metres (min.) |
| | (applies to unit 1) | |
| | only in plan 39CD-16503) | |
| | (Z.-1-162490) | |
| R6-5(48) | a) Regulations: | |
| | i) Dwelling Setback | 20 metres (66 feet) |
| | From High Pressure Pipeline | |
| | (Minimum): | |
| | ii) Main Dwelling Setback | 2.5 metres (9.8 feet) |
| | To Springmeadow Road | |
| | (Minimum): | |
| | iii) Garage Setback From | 5.5 metres (18.0 feet) |
| | Springmeadow Road | |
| | (Minimum): | |
| | (Z.-1-162502) | |

R6-5(49)

- a) Additional Permitted Uses:
Permitted uses may be developed in the form of land lease community homes.
- b) Regulations:
- i) Density (Maximum): 30 units per hectare
 - ii) Lot Frontage 0 metres
 - iii) Side yard depth to OS5 Zone (Minimum): 1.0 metre
 - iv) Side yard depth to R6-5(7) and R1-10(9) Zones (Minimum): **(Z.-1-162534)** 1.2 metres

R6-5(50)

- a) Regulations:
- i) Density (Minimum): 30 units per hectare
(Maximum): 75 units per hectare
(Z.-1-172550)

R6-5(51)

- a) Regulations:
- i) Density (Minimum): 30 units per hectare
(Maximum): 100 units per hectare
 - ii) Height (Minimum): Two (2) storeys
(Maximum): Nine (9) storeys
(Z.-1-172550)

R6-5 (52)

- a) Regulations:
- i) Front Yard Setback (Minimum): 4 metres (13.1 feet)
 - ii) West Interior Side Yard Setback (Minimum): 4.6 metres (15.0 feet)
 - iii) Rear Yard Setback to Open Space (OS1) Zone (Minimum): 10 metres (13.1 feet)
 - iv) Density (Maximum): 39 units per hectare
(Z.-1-172553)

R6-5(54) 894 Adelaide Street North

- a) Regulations for the existing building:
- i) Front Yard (Minimum) as existing
 - ii) Side Yard Setbacks (Minimum) as existing

- b) Regulations for apartment buildings:
 - i) Density (Maximum) 72 units per hectare
 - ii) Interior Side Yard Setback 5m (16ft) (Minimum)
 - iii) Height (Maximum) 10m (32ft)

(Z.-1-182670)

- R6-5(55) 1738, 1742, 1752 and 1756 Hamilton Road
 - a) Regulations:
 - i) Interior Side and Rear Yard Depth (Minimum): 5.0 metres
 - ii) Open or covered but unenclosed decks or porches not exceeding one (1) storey in height may project into the required yard no closer than 2.0 metres to lot line adjacent an Open Space (OS5) Zone.

(Z.-1-182679)

- R6-5(56) 3087 White Oak Road
 - a) Permitted Uses:
 - i) All uses within the R6-5 zone variation with the exception of apartment buildings, or cluster apartment buildings
 - b) Regulations:
 - i) Front Yard Depth (Minimum) 3m (9.8ft)
 - ii) Density (Maximum) 75 units per hectare

(Z.-1-192756)

- R6-5(57) 2054 Adelaide Street North
 - a) Regulations
 - i) Front Yard Setback, Main Dwellings (Minimum): 3 metres (9.8 feet)
 - ii) Front Yard Depth for Garages (Minimum): 5.5 metres (18.0 feet)
 - iii) Dwelling Setback From High Pressure Pipeline (Minimum): 20.0 metres (66 feet)

(Z.-1-192775 - LPAT Issued - 2018-11-05)

- R6-5(60) 58 Sunningdale Road West
 - a) Regulations:
 - i) Front and Exterior Yard Setback (Minimum): 4.5 metres
 - ii) Height Apartment Uses (Maximum): 15 metres (4 storeys)
 - iii) Density (Maximum): 100 units per hectare

- iv) Height 10.5 metres
Within 30 metres of
"Street B":
(Z.-1-192757)
- R6-5(61) 915, 965, 1031 and 1095 Upperpoint Avenue
- a) Regulations:
 - i) Front Yard Depth to Main Dwelling (Minimum): 3.0 metres
 - ii) Front and Exterior Yard Depth to Garage (Minimum): 5.5 metres
 - iii) Exterior Side Yard Depth (Minimum): 4.5 metres
 - iv) Interior Side Yard Depth (Minimum): 1.2 metres
 - v) Height (Maximum): 13 metres
 - vi) Dwelling Setback from a High Pressure Pipeline (Minimum): 20 metres
(Z.-1-192780)
- R6-5(62) 3700 Colonel Talbot Road and 3645 Bostwick Road
- a) Regulations:
 - i) Front Yard Setback, Dwelling(s)
(Minimum): 3 metres (9.8 feet)
(Maximum): 4.5 metres (14.8 feet)
 - ii) Front Yard Depth, Garages (Minimum): 6 metres (19.7 feet)
 - iii) Garages shall not project beyond the façade of the dwelling or façade (front face) of any porch, and shall not occupy more than 50% of lot frontage.
 - iv) Density (Minimum): 30 units per hectare
(Z.-1-192790)
- R6-5(63) 3700 Colonel Talbot Road and 3645 Bostwick Road
- a) Regulations:
 - i) Yard Setback (Adjacent to OS5) (Minimum): 10 metres (32.8 feet) from OS5 Zone
 - ii) Density (Minimum): 30 units per hectare
(Maximum): 65 units per hectare
 - iii) Provide built form along the OS5 Zone and orient the buildings to the open space by including individual unit doors or a main building entrance facing the open space.
 - iv) The 10 metre yard setback from the OS5 Zone will include increased landscaping as per the approved landscape plan through file 39T-17503 (3700 Colonel Talbot Road and 3645 Bostwick Road).

- v) No structures are permitted within the 10m yard setback from the OS5 Zone.
(Z.-1-19790)
- R6-5(64) 3700 Colonel Talbot Road and 3645 Bostwick Road
- a) Regulations:
 - i) Front Yard Setback, Dwelling(s)
 - (Minimum): 3 metres (9.8 feet)
 - (Maximum): 4.5 metres (14.8 feet)
 - ii) Front Yard Depth, Garages
 - (Minimum): 6 metres (19.7 feet)
 - iii) Garages shall not project beyond the façade of the dwelling or façade (front face) of any porch, and shall not occupy more than 50% of lot frontage.
 - iv) Density (Minimum): 30 units per hectare
 - v) Development shall be oriented to Bostwick Road.
(Z.-1-192790)
- R6-5(65) 3700 Colonel Talbot Road and 3645 Bostwick Road
- a) Regulations:
 - i) Front Yard Setback, Dwelling(s)
 - (Minimum): 3 metres (9.8 feet)
 - (Maximum): 4.5 metres (14.8 feet)
 - ii) Front Yard Depth, Garages
 - (Minimum): 6 metres (19.7 feet)
 - iii) Garages shall not project beyond the façade of the dwelling or façade (front face) of any porch, and shall not occupy more than 50% of lot frontage.
 - iv) Density
 - (Minimum): 30 units per hectare
 - (Maximum): 75 units per hectare
 - v) Provide built form along the OS1 Zone and orient the buildings to the open space by including individual unit doors or a main building entrance facing the open space.
(Z.-1-192790)
- R6-5(66) Northerly Portion of 943 Fanshawe Park Road West and 1800 Aldersbrook Gate
- a) Regulations:
 - i) Front Yard Depth
 - (Minimum): 2.8 Metres (9.2 feet)
 - ii) Density
 - (Maximum): 40 Units Per Hectare
- (Z.-1-202814)
- R6-5(67) 1395 Riverbend Road, described as part of Block 1 Plan 33M-743
- a) Regulations:
 - i) Front and Exterior Side Yard Depth
 - (Minimum): 3.0 metres
 - ii) Interior Side and Rear Yard Depth
 - (Minimum): 3.0 metres
 - iii) Height
 - (Maximum): 18.0 metres

- iv) Density (Maximum): 45 units per hectare
- v) Parking (Minimum): 1 space per unit
- vi) Parking may be provided by a mechanical stacked parking system; notwithstanding Section 4.19, parking provided by a mechanical stacked parking system shall be exempt from the size requirements of Section 4.19.2 - Dimensions of Parking Spaces, and no access aisles are required as per Sections 4.19.2.1 - Access Aisles and 4.19.6 (j) - Access Aisles for Parking Spaces for Persons with Disabilities. (Z.-1-202815)

R6-5(68) 58 Sunningdale Road West

- a) Regulations:
 - i) Front and Exterior Yard Setback (Minimum): 4.5 metres
 - ii) Height Apartment Uses Only (Maximum): 15 metres (4 storeys)
 - iii) Density (Maximum): 100 units per hectare
 - iv) Height: In exchange for one (1) level of underground parking (65% of required parking minimum) and a \$50,000 contribution for public art, an increased height of 22.5 m (6 storey) maximum for apartment buildings may be permitted. (Z.-1-192757)

R6-5(69) 442 Third Street

- a) Regulations
 - i) Front Yard Depth (Maximum): 3.5 metres (11.5 feet)
 - ii) North Interior Side Yard Depth (Minimum): 3.0 metres (9.8 feet) when the end wall of a unit contains no windows to habitable rooms
 - iii) Height (Maximum): 10.5m (34.5ft) (Z.-1-202856)

R6-5(70) 1200 & 1230 Hyde Park Rd

- a) Regulations
 - i) Net Density (maximum): 35 uph (based on total land area within the zone)
 - ii) Height (maximum): 14 metres (45.9 feet) (4 storeys)
 - iii) Front & Exterior Side Yard Depth (minimum): 3 metres (9.84 feet)
 - iv) Setback from Railway Right of Way (minimum): 30 metres (98.4 feet)

iv) The front face and primary entrance of dwellings shall be oriented to adjacent streets.
(Z.-1-202869)

R6-5(71) 1176, 1200 & 1230 Hyde Park Road and a portion of 1150 Gainsborough Road

a) Regulations

i) Density (maximum) 100 uph (41 units per acre)

ii) Height (maximum) 3 storey

iii) Front & Exterior Side Yard Depth (minimum) 3 metres (9.84 feet)

iv) Setback from Railway Right of Way (minimum) 30 metres (98.4 feet)

v) The front face and primary entrance of dwellings shall be oriented to adjacent streets
(Z.-1-202869)

R6-5(72) 1176 & 1200 Hyde Park Road and a portion of 1150 Gainsborough Road

a) Regulations

i) Density (maximum) 90 uph (37 units per acre)

ii) Height (maximum) 3 storey

iii) Lot Frontage (minimum) 10 metres (32.8 feet)

iv) Setback from Railway Right of Way (minimum) 30 metres (98.4 feet)
(Z.-1-202869)

TABLE 10.3

RESIDENTIAL R6 ZONE

REGULATIONS FOR R6 ZONE VARIATIONS

| Column A | | B | C | D | E | |
|----------|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|-------|---------------------|
| Line 1 | RESIDENTIAL TYPE | Cluster Housing | | | | |
| 2 | ZONE VARIATIONS | R6-1 | R6-2 | R6-3 | R6-4 | R6-5 |
| 3 | PERMITTED USES | See Section 10.2 (Z.-1-101921) | | | | |
| 4 | LOT AREA () MINIMUM | 5 000 | 2 000 | 5 000 | 2 000 | 850 |
| 5 | LOT FRONTAGE (m) MINIMUM | 22.0 | | | | 10 |
| 6 | FRONT AND EXTERIOR SIDE YARD DEPTH (m) MINIMUM | LOCAL STREET MAIN BUILDING | 6.0 | | | |
| 7 | | LOCAL STREET GARAGE | 6.0 | | | |
| 8 | | ARTERIAL | 8.0 | | | |
| 9 | | PRIMARY COLLECTOR | 6.0 | | | |
| 10 | | SECONDARY COLLECTOR | 6.0 | | | |
| 11 | INTERIOR SIDE AND REAR YARD DEPTH (m) MINIMUM (Z.1-197503) | <p>0.5 metre (1.6 feet) per 1.0 metre (3.3 feet) of main building height or fraction thereof, but in no case less than 3 metres (9.8 feet) when the wall of a unit contains no windows to habitable rooms or 6 metres (19.7 feet) when the wall of a unit contains windows to habitable rooms.</p> <p>3 metres (9.8 feet) where the wall of an end unit facing the rear yard and/or interior side yard contains windows to habitable rooms on the ground floor only and no access points to the dwelling unit along the wall facing rear yard or interior side yard (Z.1-00761)</p> | | | | SEE SECTION 10.3(1) |

| | | | | | | |
|----|-------------------------------------|------|------|------|------|------|
| 12 | LANDSCAPED OPEN SPACE (%) MINIMUM | 45 | 45 | 40 | 30 | 30 |
| 13 | LOT COVERAGE (%) MAXIMUM | 25 | 30 | 35 | 40 | 45 |
| 14 | HEIGHT (m) MAXIMUM | 10.5 | 10.5 | 10.5 | 10.5 | 12.0 |
| 15 | DENSITY - UNITS PER HECTARE MAXIMUM | 15 | 20 | 25 | 30 | 35 |

* Z.-1-94236